

## *PulsGuideJr*

**ON-OFF/Brightness:)** Rotate black knob on end clockwise to increase, Counter-clockwise to click off.

**LED Blink:** Rotate the white knob knob nearest eyepiece counterclockwise for pulse, clockwise for faster pulse and continuous on.

**Battery Installation:** Uses one Duracel XL DL1/3N lithium battery or equivalent. Pull white blink knob out of side of body, grasp black on/off knob and gently pull circuit board out. Install new battery. **Be careful of battery polarity. Inserting battery with polarity reversed will damage circuitry and void warranty.**

Remove anti-rattle foam from old battery and press on new battery. Insert circuit board into tube compressing anti-rattle foam and slide circuit board into body. You may have to rotate the circuit board as you slide it in to get the LED to slip into the hole in the front end and also to align blink potentiometer with hole in side. Insert white knob through sides of body into hole on blink potentiometer .

**1 Year limited warranty: Rigel Systems, 26850 Basswood Ave, Rancho Palos Verdes CA, 90275** warrants to the original consumer purchaser of its product that the product will be free of defects in material or workmanship 1 years from the date of purchase under normal use.

During this warranty period, **Rigel Systems** will, at its option, repair or replace the product without charge for parts or labor when delivered to **Rigel Systems** with proof of the date of purchase and a statement of the problem with the product. Shipping and handling charges to **Rigel Systems** are your responsibility.

This warranty does not apply if the product has been altered or repaired by anyone other than **Rigel Systems** or has been subjected to purchaser abuse, accident, negligence or damage subsequent to purchase including battery damage to product.

This warranty excludes incidental or consequential damages resulting from the product or use of the product. The product is not a toy. Keep away from children.