

# QuikFinder™

## Compact Reflex Sight

1. **Battery Installation:** Uses one BR2032 or CR2032 3v lithium battery or equivalent Remove QuikFinder from Baseplate
2. Insert the battery with the plus side showing – it slips under a pair of contacts — **do not press it down on top of them**
3. Reattach QuikFinder to Baseplate




**Attachment of QuikFinder to baseplate:** Holding QuikFinder at 45 degree angle to baseplate, Insert long tab on front into long slot of baseplate and rotate until catch on back of QuikFinder clips into small slot on baseplate.

**Removal of QuikFinder from baseplate:** Holding baseplate, depress button on clip on back of body and rotate forward.

**ON-OFF/Intensity:** Rotary switch located on front of QuikFinder, just below adjusting screws.

**Pulse:** Small white knob located on front of QuikFinder. Turn clockwise to pulse.


**Alignment:** Turning the three white screws on the front of the unit shift the reticule inside the view field to align the reticule with the telescope's field of view.  
**Outer ring is 2°, inner ring is 1/2°.**



# QuikFinder™

## Compact Reflex Sight

1. **Battery Installation:** Uses one BR2032 or CR2032 3v lithium battery or equivalent Remove QuikFinder from Baseplate
2. Insert the battery with the plus side showing – it slips under a pair of contacts — **do not press it down on top of them**
3. Reattach QuikFinder to Baseplate




**Attachment of QuikFinder to baseplate:** Holding QuikFinder at 45 degree angle to baseplate, Insert long tab on front into long slot of baseplate and rotate until catch on back of QuikFinder clips into small slot on baseplate.

**Removal of QuikFinder from baseplate:** Holding baseplate, depress button on clip on back of body and rotate forward.

**ON-OFF/Intensity:** Rotary switch located on front of QuikFinder, just below adjusting screws.

**Pulse:** Small white knob located on front of QuikFinder. Turn clockwise to pulse.

**Alignment:** Turning the three white screws on the front of the unit shift the reticule inside the view field to align the reticule with the telescope's field of view.  
**Outer ring is 2°, inner ring is 1/2°**



# QuikFinder™

## Compact Reflex Sight

1. **Battery Installation:** Uses one BR2032 or CR2032 3v lithium battery or equivalent Remove QuikFinder from Baseplate
2. Insert the battery with the plus side showing – it slips under a pair of contacts — **do not press it down on top of them**
3. Reattach QuikFinder to Baseplate




**Attachment of QuikFinder to baseplate:** Holding QuikFinder at 45 degree angle to baseplate, Insert long tab on front into long slot of baseplate and rotate until catch on back of QuikFinder clips into small slot on baseplate.

**Removal of QuikFinder from baseplate:** Holding baseplate, depress button on clip on back of body and rotate forward.


**ON-OFF/Intensity:** Rotary switch located on front of QuikFinder, just below adjusting screws.

**Pulse:** Small white knob located on front of QuikFinder. Turn clockwise to pulse.

**Alignment:** Turning the three white screws on the front of the unit shift the reticule inside the view field to align the reticule with the telescope's field of view.  
**Outer ring is 2°, inner ring is 1/2°.**



**Making sure it is working:** (1) Go in a dimly lit room. Turn the small white knob fully counter clockwise (2) Turn the black knob fully clockwise (full brightness) (3) look at the bottom of the Quikfinder , do you see a red glow coming around the battery holder? Then the LED is lighting . (4) Now hold the Quikfinder up to your eye with the knobs pointing away from you. You should see 2 red rings.



**Attachment to telescope:** Cut and apply double sided adhesive foam tape to rails on baseplate for adhesive mounting to telescope.


**Alternative Mounting Methods:** Hole on baseplate can be used for screw mounting to telescope. For small scopes, single sided adhesive foam tape can be applied to rails on baseplate and cable ties (available at electronic and hardware stores) used to attach baseplate to telescope.

**Care:** Do not let sunlight shine directly into the lens — it will melt the reticule. Treat lens and view field as you would any optical element of your telescope. clean with soft cloth only.

**Ordering Additional Baseplates:** Additional baseplates are \$6 each. Please specify diameter of telescope tube when ordering. Shipping is \$3.

**1 Year limited warranty: Rigel Systems,** warrants to the original consumer purchaser of its product that the product will be free of defects in material or workmanship 1 years from the date of purchase under normal use. During this warranty period, **Rigel Systems** will, at its option, repair or replace the product without charge for parts or labor when delivered to **Rigel Systems** with proof of the date of purchase and a statement of the problem with the product. Shipping and handling charges to **Rigel Systems** are your responsibility. This warranty does not apply if the product has been altered or repaired by anyone other than **Rigel Systems** or has been subjected to purchaser abuse, accident, negligence or damage subsequent to purchase including battery damage to product. This warranty excludes incidental or consequential damages resulting from the product or use of the product. The product is not a toy. Keep away from children.

**Making sure it is working:** (1) Go in a dimly lit room. Turn the small white knob fully counter clockwise (2) Turn the black knob fully clockwise (full brightness) (3) look at the bottom of the Quikfinder , do you see a red glow coming around the battery holder? Then the LED is lighting . (4) Now hold the Quikfinder up to your eye with the knobs pointing away from you. You should see 2 red rings.



**Attachment to telescope:** Cut and apply double sided adhesive foam tape to rails on baseplate for adhesive mounting to telescope.


**Alternative Mounting Methods:** Hole on baseplate can be used for screw mounting to telescope. For small scopes, single sided adhesive foam tape can be applied to rails on baseplate and cable ties (available at electronic and hardware stores) used to attach baseplate to telescope.

**Care:** Do not let sunlight shine directly into the lens — it will melt the reticule. Treat lens and view field as you would any optical element of your telescope. clean with soft cloth only.

**Ordering Additional Baseplates:** Additional baseplates are \$6 each. Please specify diameter of telescope tube when ordering. Shipping is \$3.

**1 Year limited warranty: Rigel Systems,** warrants to the original consumer purchaser of its product that the product will be free of defects in material or workmanship 1 years from the date of purchase under normal use. During this warranty period, **Rigel Systems** will, at its option, repair or replace the product without charge for parts or labor when delivered to **Rigel Systems** with proof of the date of purchase and a statement of the problem with the product. Shipping and handling charges to **Rigel Systems** are your responsibility. This warranty does not apply if the product has been altered or repaired by anyone other than **Rigel Systems** or has been subjected to purchaser abuse, accident, negligence or damage subsequent to purchase including battery damage to product. This warranty excludes incidental or consequential damages resulting from the product or use of the product. The product is not a toy. Keep away from children.

**Making sure it is working:** (1) Go in a dimly lit room. Turn the small white knob fully counter clockwise (2) Turn the black knob fully clockwise (full brightness) (3) look at the bottom of the Quikfinder , do you see a red glow coming around the battery holder? Then the LED is lighting . (4) Now hold the Quikfinder up to your eye with the knobs pointing away from you. You should see 2 red rings.



**Attachment to telescope:** Cut and apply double sided adhesive foam tape to rails on baseplate for adhesive mounting to telescope.

**Alternative Mounting Methods:** Hole on baseplate can be used for screw mounting to telescope. For small scopes, single sided adhesive foam tape can be applied to rails on baseplate and cable ties (available at electronic and hardware stores) used to attach baseplate to telescope.

**Care:** Do not let sunlight shine directly into the lens — it will melt the reticule. Treat lens and view field as you would any optical element of your telescope. clean with soft cloth only.

**Ordering Additional Baseplates:** Additional baseplates are \$6 each. Please specify diameter of telescope tube when ordering. Shipping is \$3.

**1 Year limited warranty: Rigel Systems,** warrants to the original consumer purchaser of its product that the product will be free of defects in material or workmanship 1 years from the date of purchase under normal use. During this warranty period, **Rigel Systems** will, at its option, repair or replace the product without charge for parts or labor when delivered to **Rigel Systems** with proof of the date of purchase and a statement of the problem with the product. Shipping and handling charges to **Rigel Systems** are your responsibility. This warranty does not apply if the product has been altered or repaired by anyone other than **Rigel Systems** or has been subjected to purchaser abuse, accident, negligence or damage subsequent to purchase including battery damage to product. This warranty excludes incidental or consequential damages resulting from the product or use of the product. The product is not a toy. Keep away from children.